



Tableau des profondeurs de champ IBELUX 40mm / 1: 0,85

Distance en cm

Distance en cm

Indice d'ouverture

	0	75	100	120	140	170	200	250	350	500	800	1000	1500
0.85	73.9 - 76.2	98.0 - 102.1	117.1 - 123.0	136.1 - 144.2	164.2 - 176.2	192.0 - 208.7	237.6 - 263.8	326.0 - 377.8	452.3 - 558.9	684.3 - 962.9	825.3 - 1268.5	1138.2 - 2199.1	
1	73.7 - 76.4	97.7 - 102.5	116.6 - 123.6	135.4 - 145.0	163.2 - 177.4	190.7 - 210.3	235.5 - 266.4	322.1 - 383.1	444.8 - 570.8	667.2 - 998.8	800.6 - 1331.6	1091.7 - 2396.2	
1.4	73.2 - 76.9	96.8 - 103.5	115.3 - 125.1	133.6 - 147.0	160.7 - 180.5	187.2 - 214.7	230.2 - 273.6	312.2 - 398.2	426.0 - 605.0	625.7 - 1109.0	741.5 - 1535.2	984.5 - 3148.6	
2	72.4 - 77.8	95.4 - 105.1	113.4 - 127.4	131.1 - 150.2	157.0 - 185.4	182.2 - 221.7	222.6 - 285.1	298.4 - 423.2	400.6 - 664.9	572.3 - 1329.0	667.6 - 1992.0	858.1 - 5952.4	
2.8	71.5 - 78.9	93.7 - 107.2	111.0 - 130.6	127.8 - 154.7	152.3 - 192.4	175.9 - 231.8	213.3 - 302.0	281.8 - 461.9	371.1 - 765.9	513.7 - 1806.7	589.2 - 3302.5	732.7 - ∞	
4	70.0 - 80.7	91.2 - 110.6	107.5 - 135.8	123.2 - 162.0	145.8 - 203.8	167.2 - 248.8	200.6 - 331.6	260.0 - 535.2	334.2 - 992.1	445.4 - 3921.6	501.0 - 250000.0	601.0 - ∞	
5.6	68.2 - 83.3	88.2 - 115.5	103.2 - 143.3	117.6 - 173.0	137.9 - 221.5	157.0 - 275.6	186.0 - 381.3	235.8 - 678.8	295.1 - 1636.1	378.4 - ∞	417.6 - ∞	484.8 - ∞	
8	65.7 - 87.4	83.9 - 123.8	97.4 - 156.3	110.1 - 192.3	127.6 - 254.5	143.7 - 329.0	167.6 - 492.1	206.9 - 1136.4	251.0 - 62500.0	308.6 - ∞	334.2 - ∞	375.8 - ∞	
11	62.8 - 93.2	79.1 - 135.9	91.0 - 176.2	101.9 - 223.6	116.7 - 312.8	130.0 - 433.8	149.1 - 772.8	179.4 - 7216.5	211.5 - ∞	250.9 - ∞	267.5 - ∞	293.3 - ∞	
16	58.4 - 104.8	72.3 - 162.3	82.0 - 223.9	90.7 - 307.0	102.2 - 506.0	112.1 - 926.0	126.0 - 15625.0	146.8 - ∞	167.6 - ∞	191.2 - ∞	200.6 - ∞	214.8 - ∞	
22	53.9 - 123.1	65.5 - 211.9	73.3 - 331.5	80.1 - 555.6	88.9 - 1954.0	96.3 - ∞	106.3 - ∞	120.6 - ∞	134.1 - ∞	148.8 - ∞	154.4 - ∞	162.6 - ∞	